

Datasheet revision 1.0

www.chipquik.com

Liquid Flux No-Clean in 30ml (1.0oz) Squeeze Bottle w/tip

Product Highlights A liquid flux that is non-flammable No-Clean Water-Based, leaves no residues VOC Free, Halide Free, Rosin Free Ideal for all rework, solder, and de-solder applications Excellent wetting Easily cleaned with isopropyl alcohol (IPA) Can be used with Leaded and Lead-Free applications RoHS II and REACH compliant



Specifications

Flux Type: Flux Classification: Packaging: Shelf Life: No-Clean Liquid Flux (for Leaded and Lead-Free applications) INM0 30ml Squeeze Bottle Refrigerated >24 months, Unrefrigerated >24 months

Storage and Handling

Store refrigerated or at room temperature 3-25°C (37-77°F). The liquid flux can be allowed to freeze. Freezing will not degrade this product. Allow 4 hours for flux to reach an operating temperature of 20-25°C (68-77°F) before use.

Transportation

This product has no shipping restrictions. Shipping below 0°C (32°F) or above 25°C (77°F) for normal transit times by ground or air will not impact this product's stated shelf life.

Cleaning This is a no-clean liquid flux, post-use cleaning is not required.

Conforms to the following Industry Standards:	
J-STD-004B, Amendment 1 (Solder Fluxes):	Yes
RoHS 2 Directive 2011/65/EU:	Yes