

Tripp Lite 1111 W. 35th Street Chicago, IL 60609 USA Telephone: 773.869.1234 www.tripplite.com

## **BP36V27 - External Battery Pack for UPS System**

### MODEL NUMBER: **BP36V27**





#### Highlights

- Extends runtime of select compatible Tripp Lite UPS Systems with 36V DC external battery connector
- Provides daisy-chain capability
- Simple installation; tower and stack adaptable
- 2 year warranty

#### **Package Includes**

- BP36V27 external battery pack
- Warranty information
- Instruction manual

#### Description

BP36V27 tower external battery pack offers extended battery runtime when used in conjunction with Tripp Lite SMART750XL, SMART1050XL & SMART1500XL UPS systems supporting a 36V external battery connection. Includes heavy gauge cabling with high current DC connectors for simple installation. Additional output connector allows multiple BP36V27 battery packs to be daisy-chained to the UPS for even longer extended run operation.

COMPATIBLE UPS SYSTEMS: SMART750XL, SMART1050XL, SMART1500XL, SMARTINT1400XL and other Tripp Lite UPS systems that specify the use of this battery pack.

#### Features

- Offers extended-run UPS operation when used in conjunction with compatible Tripp Lite UPS systems
- Set of two input/output connectors allows multiple BP36V27 battery packs to be daisy-chained to the UPS for even longer extended run operation
- Pre-wired internal battery sets are ready for installation with no user battery connections required
- Includes heavy gauge cabling with high current DC connectors for simple installation
- Matches cabinet appearance of the companion UPS
- 2 year warranty

# **Specifications**

OVERVIEW		
UPC Code	037332219800	
BATTERY		
Expandable Battery Runtime	Gray 50 amp female DC connector for additional battery packs	
DC System Voltage (VDC)	36	



UPS Connection	Attached cable with grey 50 amp DC connector	
Typical Battery Lifespan	4-6 years typical (North America)	
PHYSICAL		
Shipping Dimensions (hwd / in.)	0.000 × 0.000 × 0.000	
Shipping Weight (lbs.)	0.0000	
Shipping Weight (kg)	0.00	
Unit Dimensions (hwd / in.)	7 x 8.5 x 14.5	
Unit Dimensions (hwd / cm)	17.8 x 21.6 x 36.9	
Unit Weight (Ibs.)	56.4	
Unit Weight (kg)	25.58	
Material of Construction	Black polycarbonate	
Form Factors Supported	Floorstanding tower format, stackable - supports wallmount with optional <a <br="" class="productLink">href="//www.tripplite.com/Wall-Mount-Bracket-Installation-Accessories-for-UPS- Systems~UPSWM"&gt;UPSWM</a> accessory	
CERTIFICATIONS		
Certifications	Tested to UL, cUL, CE, NOM	
WARRANTY		
Product Warranty Period (Worldwide)	2-year limited warranty	
Optional Coverage	3 year, 5 year, next day and on-site warranty coverage available	

© 2018 Tripp Lite. All rights reserved. All product and company names are trademarks or registered trademarks of their respective holders. Use of them does not imply any affiliation with or endorsement by them. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Tripp Lite uses primary and third-party agencies to test its products for compliance with standards. See a list of Tripp Lite's testing agencies: https://www.tripplite.com/products/product-certification-agencies