

Customer Specification



Part Number: BR-1.5-14WSS

Product Description: BRIDLE RING WITH SADDLE - 1 1/2" CAPACITY - MOUNTS WITH #14 WOOD SCREW THREAD

Neterial Specifications Type: Assembly Color: Various Enterial Specifications Enterial Specifications Color: Color: Various Enterial Specifications Compatible Wires and Cables Tapped Holes: Drop Wire: Clearance Holes (in): Drop Wire: Clearance Holes (in): Plain Rod (in): Threaded Rod Size (in): Metal Stud Size (in): Metal Stud Size (in): Rigid/IMC (in): Static Load Rating Conter to Regulatory Vertical (lbs): 1-1/2 bridle ring with saddle, self tapping wood thread Horizontal (lbs): 1-1/2 bridle ring with saddle, self tapping wood thread Box Size: 8.25 X 6.25 X 6 Box Size: 8.25 X 6.25 X 6 Decument Information Decemption Created By: DIW Approved By: KLN Customer Specification #: CiteKed By: DIW Approved By: KLN Customer Specification #: CiteKed By: DIW					
Type: Assembly Finish: Assembly Color: Various Eunction Specifications Eunction Specifications Compatible Wires and Cables Threaded Rods and Bolts AC/MC CABLE (OD): Tapped Holes: Image Rods and Bolts Drop Wire: Clearance Holes (in): Image Rods (in): Drop Wire: Compatible Conduit Compatible Flanges and Studs Compatible Conduit Compatible Flange Size (in): Image Rods (in): Compatible Conduit Compatible Conduit Size (in): Image Rods (in): Compatible Conduit Compatible Flange Size (in): Image Rods (in): Rigid/IMC (in): Static Load Rating Other Vertical (lbs): Image Rods (in): Image Rods (in): Vertical (lbs): Image Rods (in): Image Rods (in): Regulatory Ul/cUL Country of Origin: US Regulatory Ul/cUL Country of Origin: Image Rods (in): Size X 6.25 X 6 Other Image Rods (in): Image Rods (in): Box Size: 8.25 X 6.25 X 6 Other Image Rods (in): Created By: DBLA	Material Specifications				
Color: Various Eunction Specifications Compatible Wires and Cables Threaded Rods and Bolts AC/MC CABLE (OD): Tapped Holes: []] Drop Wire: Clearance Holes (in): []] Plain Rod (in): Compatible Conduit Clearance Holes (in): []] Compatible Conduit Compatible Flanges and Studs Threaded Rod Size (in): []] EMT Size (in): Compatible Conduit Compatible Flanges and Studs Flange Size (in): []] Kigid/INC (in): Static Load Rating Other Vertical (lbs): Codes and Regulatory Other Vertical (lbs): Codes and Regulatory U/cuL Country of Origin: US Regulatory Ul/cuL Country of Origin: US Solution Decument Information Pieces per Package: Sol Sol Box Size: Size S & 6 Other Sol Sol Created By: BBLA Customer Specification #: Cl1447 Approved By: KLN ECN #: GAECNO1813	Type:	-		Assembly	
Function SpecificationsCompatible Wires and CablesInreaded Rods and BotsAC/MC CABLE (OD)Tapped Holes:Tapped Holes:Drop Wire:Clearance Holes (in):Clearance Holes (in):Drop Wire:Threaded Rod Size (in):Clearance Holes (in):Plain Rod (in):Threaded Rod Size (in):Clearance Holes (in):Pain Rod (in):Compatible ConduitCompatible Flanges and StudsEMT Size (in):Static Load RatingOtherVertical (lbs):Infraded Rod Size (in):Infraded Rod Size (in):Metal Stud Size (ins):Static Load RatingOtherVertical (lbs):Infrades Country of Origin:IsMetal Stud Size (ins):Static Load RatingCountry of Origin:IsMetal Stud Size (ins):Static Load RatingStatic Load RatingStatic Load RatingStatic Load RatingMetal Stud Size (ins):Static Load RatingCountry of Origin:IsStatic Load RatingStatic Load RatingStatic Load RatingStatic Load RatingMetal Stud Size (ins):Static Load RatingStatic Load RatingStatic Load RatingMetal Stud Size (ins):Static Load RatingStatic Load RatingStatic Load RatingMetal Stud Size (ins):Static Load RatingStatic Load RatingStatic Load RatingMetal Stud Size (ins):Static Load RatingStatic Load RatingStatic Load RatingMetal Stud Size (ins):Static Load RatingStatic Load RatingStatic Load RatingMetal Stud Size (ins):Static Load				,	
Compatible Wires and CablesThreaded RotsAC/MC CABLE (OD):Tapped Holes:Drop Wire:Clearance Holes (in):Drop Wire:Threaded Rod Size (in):Plain Rod (in):Threaded Rod Size (in):EMT Size (in):Flange Size (in):Rigid/IMC (in):Flange Size (in):Static Load RatingOtherVertical (lbs):1-1/2 bridle ring with saddLise Is If tapping wood threadHorizontal (lbs):1-1/2 bridle ring with saddLise Is If tapping wood threadCodes and RegulatoryCountry of Origin:Vertical (lbs):Vul/cULCodes and RegulatorySeries Size Size Size Size Size Size Size Size	Color:	Various			
AC/MC CABLE (OD): AC/MC CABLE (OD): AC/MC CABLE (OD): AC/MC CABLE (OD): ACCOMPTIBIE (CONSTRUCT CONSTRUCT C	Function Specifications				
Drop Wire: Clearance Holes (in): Plain Rod (in): Threaded Rod Size (in): Compatible Conduit Compatible Flanges and Studs EMT Size (in): Flange Size (in): Rigid/IMC (in): Static Load Rating Vertical (Ibs): 1-1/2 bridle ring with saddle, Self tapping wood thread Horizontal (Ibs): 1-1/2 bridle ring with saddle, Self tapping wood thread Vertical (Ibs): 1-1/2 bridle ring with saddle, Self tapping wood thread Horizontal (Ibs): 1-1/2 bridle ring with saddle, Self tapping wood thread Wertical (Ibs): 1-1/2 bridle ring with saddle, Self tapping wood thread Horizontal (Ibs): 1-1/2 bridle ring with saddle, Self tapping wood thread Begulatory UL/cUL Country of Origin: US Seeneral Packaging: Saz5 x 6.25 x 6 Other Box Features: So Box Size: 8.25 x 6.25 x 6 Other Box Features: So Box Size: BLA Customer Specification #: C11447 Checked By: JJW Revision Leve! 0 Approved By: KLN EN # So 6AECN01813	Compatible Wires and Cables Threaded Rods and Bolts				
Plain Rod (in):Threaded Rod Size (in):Compatible ConduitCompatible Flarges and StudsEMT Size (in):Flange Size (in):Rigid/IMC (in):Metal Stud Size (ins):Static Load RatingOtherVertical (lbs):1-1/2 bridle ring with saddle. Self tapping wood threadHorizontal (lbs):1-1/2 bridle ring with saddle.RegulatoryUL/cULCountry of Origin:General Packaging:Cardboard BoxBox Size:8.25 X 6.25 X 6Document InformationSelf cardboard BoxCreated By:DBLACustomer Specification #:Created By:DBLACustomer Specification #:Checked By:DJWRevision Leve!Approved By:KLNECN #:GateCN01813	AC/MC CABLE (OD):		Tapped Holes:		
Compatible ConduitCompatible Flarges and StudsEMT Size (in):Flange Size (in):Rigid/IMC (in):Metal Stud Size (ins):Static Load RatingOtherVertical (lbs):1-1/2 bridle ring with saddle, Self tapping wood threadHorizontal (lbs):1-1/2 bridle ring with saddle, Self tapping wood threadMetal Stud Size (in):1-1/2 bridle ring with saddle, Self tapping wood threadHorizontal (lbs):1-1/2 bridle ring with saddle, Self tapping wood threadMetal Stud Size (in):1-1/2 bridle ring with saddle, Self tapping wood threadHorizontal (lbs):1-1/2 bridle ring with saddle, Self tapping wood threadMetal Stud Size (in):1-1/2 bridle ring with saddle, Self tapping wood threadMetal Stud Size (in):1-1/2 bridle ring with saddle, Self tapping wood threadMetal Stud Size (in):1-1/2 bridle ring with saddle, Self tapping wood threadMetal Stud Size (in):1-1/2 bridle ring with saddle, Self tapping wood threadMetal Stud Size (in):1-1/2 bridle ring with saddle, Self tapping wood threadMetal Stud Size (in):1-1/2 bridle ring with saddle, Self tapping wood threadMetal Stud Size (in):1-1/2 bridle ring with saddle, Self tapping wood threadMetal Stud Size (in):1-1/2 bridle ring with saddle, Self tapping wood threadMetal Stud Size (in):1-1/2 bridle ring with saddle, Self tapping wood threadMetal Stud Size (in):1-1/2 bridle ring with saddle, Self tapping wood threadMetal Stud Size (in):1-1/2 bridle ring with saddle, Self tapping wood threadBox Size (Size Size (Size (in)):1-1/2 bridl	Drop Wire:		Clearance Holes (in):		
EMT Size (in): Rigid/IMC (in):Flange Size (in): Metal Stud Size (ins):Static Load RatingOtherVertical (lbs): Horizontal (lbs):1-1/2 bridle ring with saddle, Self tapping wood threadMetal Stud Ibs):1-1/2 bridle ring with saddle, Self tapping wood threadMetal Stud Ibs):1-1/2 bridle ring with saddle, Self tapping wood threadMetal Stud Ibs):1-1/2 bridle ring with saddle, Self tapping wood threadMetal Stud Ibs):1-1/2 bridle ring with saddle, Self tapping wood threadMetal Stud Ibs):1-1/2 bridle ring with saddle, Self tapping wood threadMetal Stud Ibs):1-1/2 bridle ring with saddle, Self tapping wood threadMetal Stud Ibs):1-1/2 bridle ring with saddle, Self tapping wood threadMetal Stud Ibs):1-1/2 bridle ring with saddle, Self tapping wood threadMetal Stud Ibs):1-1/2 bridle ring with saddle, Self tapping wood threadMetal Stud Ibs):1-1/2 bridle ring with saddle, Self tapping wood threadMetal Stud Ibs):1-1/2 bridle ring with saddle, Self tapping wood threadMetal Stud Ibs):1-1/2 bridle ring with saddle, Self tapping wood threadMetal Stud Ibs):1-1/2 bridle ring with saddle, Self tapping wood threadMetal Stud Ibs):1-1/2 bridle ring with saddle, Self tapping wood threadMetal Stud Ibs):1-1/2 bridle ring with saddle, Self tapping wood threadMetal Stud Ibs):1-1/2 bridle ring with saddle, Self tapping wood threadMetal Stud Ibs):1-1/2 bridle ring with saddle, Self tapping wood threadMetal Stud Ibs):1-1/2 bridle ring with saddle, Self tapping wood thread	Plain Rod (in):		Threaded Rod Size (in):		
Rigid/IMC (in):Metal Stud Size (ins):Static Load RatingOtherVertical (lbs):1-1/2 bridle ring with saddle, Self tapping wood threadHorizontal (lbs):1-1/2 bridle ring with saddle, Self tapping wood threadKegulatory Certifications:UL/cULCountry of Origin:Vertical (lbs):UL/cULCountry of Origin:Segulatory Certifications:UL/cULSelf tapping wood threadBeneral Packaging: Box Size:Saddle Sox 8.25 X 6.25 X 6Pieces per Package: Other Box Features:Sereated By: Checked By: Approved By:DBLACustomer Specification # Customer Specification # Custom Level:MutherDJWECN # GAECN01813		Compatible Conduit	Compatible Flanges and Studs		
Static Load RatingOtherVertical (lbs):1-1/2 bridle ring with saddle, Self tapping wood threadHorizontal (lbs):1-1/2 bridle ring with saddle, Self tapping wood threadRegulatory Certifications:UL/cULCountry of Origin:WL/cULCountry of Origin:USSeneral Packaging: Box Size:Sadboard BoxPieces per Package: Other Box Features:Box Size:S25 X 6.25 X 6Other Box Features:Created By: Checked By:DBLACustomer Specification #: Customer Specification #:Created By: Approved By:MuECN #:General Packaging: Country of BLACustomer Specification #: Customer Specification #: Customer Specification #:	EMT Size (in):		Flange Size (in):		
Vertical (lbs):1-1/2 bridle ring with saddle, Self tapping wood threadHorizontal (lbs):1-1/2 bridle ring with saddle, Self tapping wood threadCodes and Regulatory Certifications:UL/cULCountry of Origin:UL/cULCountry of Origin:USPackagingGeneral Packaging: Box Size:Cardboard BoxPieces per Package: Other Box Features:Document Information50Created By: Checked By:DBLACustomer Specification #: OC11447Checked By: Approved By:DACustomer Specification #: COUNTEDC11447	Rigid/IMC (in):		Metal Stud Size (ins):		
Vertical (lbs):1-1/2 bridle ring with saddle, Self tapping wood threadHorizontal (lbs):1-1/2 bridle ring with saddle, Self tapping wood threadCodes and RegulatoryRegulatory Certifications:UL/cULCountry of Origin:USPackaging Box Size:Cardboard Box Box Size:Pieces per Package: Other Box Features:Document InformationCreated By: Checked By: DJWDBLACustomer Specification #: OC11447Checked By: Approved By:KLNECN #:GAECN01813		Static Load Rating	<u>Other</u>		
Codes and RegulatoryRegulatory Certifications:UL/cULCountry of Origin:USPackaging:Cardboard BoxPieces per Package:50Box Size:8.25 X 6.25 X 6Other Box Features:Image: Control of Control	Vertical (lbs):		1-1/2 bridle ring with saddle	, Self tapping wood thread	
Regulatory Certifications:UL/cULCountry of Origin:USPackaging: Ofter Box Size:Cardboard BoxPieces per Package: Other Box Features:Box Size:8.25 X 6.25 X 6Other Box Features:50Document InformationCreated By:DBLACustomer Specification #: Revision Level:C11447Checked By:DJWRevision Level:0Approved By:KLNECN #:GAECN01813	Horizontal (lbs):				
Regulatory Certifications:UL/cULCountry of Origin:USPackaging: Ofter Box Size:Cardboard BoxPieces per Package: Other Box Features:Box Size:8.25 X 6.25 X 6Other Box Features:50Document InformationCreated By:DBLACustomer Specification #: Revision Level:C11447Checked By:DJWRevision Level:0Approved By:KLNECN #:GAECN01813					
Certifications:PackagingGeneral Packaging:Cardboard BoxBox Size:Cardboard Box8.25 X 6.25 X 6Other Box Features:Document InformationCreated By:DBLACreated By:DBLAChecked By:DJWApproved By:KLNKLNECN #:GAECN01813				[]	
PackagingGeneral Packaging:Cardboard BoxPieces per Package:50Box Size:8.25 X 6.25 X 6Other Box Features:100Document InformationCreated By:DBLACustomer Specification #:C11447Checked By:DJWRevision Level:0Approved By:KLNECN #:GAECN01813		UL/cUL	Country of Origin:	US	
General Packaging:Cardboard BoxPieces per Package:50Box Size:8.25 X 6.25 X 6Other Box Features:50Document InformationCreated By:DBLACustomer Specification #:C11447Checked By:DJWRevision Level:0Approved By:KLNECN #:GAECN01813					
Box Size:8.25 X 6.25 X 6Other Box Features:Document InformationCreated By:DBLACustomer Specification #:C11447Checked By:DJWRevision Level:0Approved By:KLNECN #:GAECN01813	General Packaging			50	
Document InformationCreated By:DBLACustomer Specification #:C11447Checked By:DJWRevision Level:0Approved By:KLNECN #:GAECN01813				50	
Created By:DBLACustomer Specification #:C11447Checked By:DJWRevision Level:0Approved By:KLNECN #:GAECN01813					
Checked By:DJWRevision Level:0Approved By:KLNECN #:GAECN01813	Croated By:			C11447	
Approved By: KLN ECN #: GAECN01813	-		-		
	Аррготей ву:				