


### Absolute maximum ratings


( $T_a=25^\circ\text{C}$ )

Symbol	Ratings		Unit
	N channel	P channel	
$V_{DSS}$	60	-60	V
$V_{GSS}$	$\pm 20$	$\mp 20$	V
$I_D$	4	-4	A
$I_{D(\text{pulse})}$	8 (PW≤1ms, Duty≤1%)	-8 (PW≤1ms, Duty≤1%)	A
$P_T$	4 ( $T_a=25^\circ\text{C}$ , with all circuits operating, without heatsink)		W
	28 ( $T_c=25^\circ\text{C}$ , with all circuits operating, with infinite heatsink)		W
$\theta_{j-a}$	31.25 (Junction-Air, $T_a=25^\circ\text{C}$ , with all circuits operating)		°C/W
$\theta_{j-c}$	4.46 (Junction-Case, $T_c=25^\circ\text{C}$ , with all circuits operating)		°C/W
$T_{ch}$	150		°C
$T_{stg}$	-40 to +150		°C

### ■ Equivalent circuit diagram



### Characteristic curves



## Electrical characteristics

(Ta=25°C)

Symbol	N channel						P channel					
	Specification			Unit	Conditions	Specification			Unit	Conditions		
	min	typ	max			min	typ	max				
V(BR)DSS	60			V	Id=100μA, Vgs=0V	-60			V	Id=-100μA, Vgs=0V		
IGSS			±10	μA	Vgs=±20V			±10	μA	Vgs=±20V		
IBSS			100	μA	Vds=60V, Vgs=0V			-100	μA	Vds=-60V, Vgs=0V		
VTH	1.0		2.0	V	Vds=10V, Id=250μA	-1.0		-2.0	V	Vds=-10V, Id=-250μA		
Re(yfs)		2.5		S	Vds=10V, Id=2A		3		S	Vds=10V, Id=-2A		
RDS(ON)			0.55	Ω	Vgs=4V, Id=2A		0.55		Ω	Vgs=-10V, Id=-2A		
Ciss		150		pF	Vds=10V		320		pF	Vds=-10V,		
Coss		70		pF	f=1.0MHz		130		pF	f=1.0MHz,		
Crss		15		pF	Vgs=0V		40		pF	Vgs=0V		
td (on)		12		ns	Id=2A, Vdd=−20V, RL=10Ω, Vgs=5V, see Fig.3 on page 16.		20		ns	Id=−2A, Vdd=−20V, RL=10Ω, Vgs=−5V, see Fig.4 on page 16.		
tr		40		ns			95		ns			
td (off)		40		ns			70		ns			
tr		25		ns			60		ns			
VSD		1.2		V	Isd=4A, Vgs=0V		-1.1		V	Isd=−4A, Vgs=0V		
trr		75		ns	Isd=2A, Vgs=0V, di/dt=100A/μs		75		ns	Isd=−2A, Vgs=0V, di/dt=100A/μs		

## Characteristic curves

