

Datasheet revision 1.0 www.chipquik.com

# Liquid Flux Water Washable in 30ml (1.0oz) Squeeze Bottle w/tip

## Product Highlights

A liquid flux that is non-flammable
Low solids
Water soluble
Highly activated rosin
VOC Free
Ideal for all rework, solder, and de-solder applications
Excellent wetting
Easily cleaned with water or isopropyl alcohol (IPA)
Can be used with Leaded and Lead-Free applications
RoHS II and REACH compliant



# Specifications

Flux Type: Water Washable Liquid Flux (for Leaded and Lead-Free applications)
Flux Classification: ROM1 (Water Soluble, Must be cleaned off post-use using Water or IPA)

Packaging: 30ml Squeeze Bottle

Shelf Life: Refrigerated >24 months, Unrefrigerated >24 months

## Storage and Handling

Store refrigerated or at room temperature 3-25°C (37-77°F). The liquid flux can be allowed to freeze. Freezing will not degrade this product. Allow 4 hours for flux to reach an operating temperature of 20-25°C (68-77°F) before use.

#### Transportation

This product has no shipping restrictions. Shipping below 0°C (32°F) or above 25°C (77°F) for normal transit times by ground or air will not impact this product's stated shelf life.

#### Cleaning

This is a water soluble liquid flux, post-use cleaning is required. Clean with water or isopropyl alcohol (IPA).

### Conforms to the following Industry Standards:

J-STD-004B, Amendment 1 (Solder Fluxes):

RoHS 2 Directive 2011/65/EU:

Yes

Yes