

Wire-wound Chip Power Inductors (CB series)[CBC]

CBC3225T330MR



■ Features

- Item Summary
33 μ H \pm 20%, 0.5A, 1210/3225 (EIA/JIS)
- Lifecycle Stage
Mass Production
- Standard packaging quantity (minimum)
Taping Embossed 1000pcs

■ Products characteristics table

Inductance	33 μ H \pm 20 %
Case Size (EIA/JIS)	1210/3225
Rated Current (max)	0.5 A
Saturation Current (max)	0.5 A
Temperature Rise Current (max)	0.57 A
DC Resistance (max)	0.533 Ω
DC Resistance (typ)	0.41 Ω
LQ Measuring Frequency	0.1 MHz
Self Resonant Frequency (min)	13 MHz
Operating Temp. Range	-40 to +105 $^{\circ}$ C (Including-self-generated heat)
Temperature characteristic (Inductance change)	\pm 20 %
RoHS2 Compliance (10 subst.)	Yes
REACH Compliance (173 subst.)	Yes
Halogen Free	Yes
Soldering	Reflow

■ External Dimensions

Dimension L	3.2 \pm 0.2 mm
Dimension W	2.5 \pm 0.2 mm
Dimension T	2.5 \pm 0.2 mm
Dimension e	0.6 \pm 0.3 mm

2017.04.30

The data is reference only. Electrical characteristics vary depending on environment or measurement condition.
 TAIYO YUDEN reserves the right to make change to the Date at any time without notice.
 Before making final selection, please check product specification.




Wire-wound Chip Power Inductors (CB series)

CBC3225T330MR



Dimension	unit : mm	unit : inch
Length :	3.2 +/- 0.2	(0.126 +/- 0.008)
Width :	2.5 +/- 0.2	(0.098 +/- 0.008)
Height :	2.5 +/- 0.2	(0.098 +/- 0.008)

Inductance :	33	uH (test freq at 0.1MHz)
DC Resistance :	0.41 / 0.533	ohm (typ / max)
Saturation Current :	500	mA (max)
Temp. rise Current :	570	mA (max)
Saturation current typical : 30% reduction from initial L value.		
Temp rise Current typical : Temperature will rise by 40 deg C		



The data is reference only. Electrical characteristics vary depending on environment or measurement condition. TAIYO YUDEN reserves the right to make change to the data at any time without notice. Before making final selection, please check product specification.